

REINE PRODUCT SPECIFICATION

GLAZED FLOOR TILE 60x60cm, 30x60cm, 30x30cm, 60x120cm
 Pressed Ceramic Tiles International Norms ISO 13006-10545/98
 GROUP: B1b

REINE

No.	Icon	Test item	Unit	Requirements of Standard	Test result	Result	
1		Dimensional variation	(%)	length of side	0.6	< 0.6	Qualified
2		Side straightness	(%)	± 0.5		< 0.5	Qualified
3		Squareness	(%)	± 0.5		< 0.5	Qualified
4		Surface flatness	(%)	Center curvature degree	± 0.5	< 0.5	Qualified
				Warping degree	± 0.5	< 0.5	Qualified
				Side curvature degree	± 0.5	< 0.5	Qualified
5		Surface quality	—	Sighting vertically at a distance of 0.8 meter away from the tile no defect on surface is observed in at least 95% of the tile	conformed	Qualified	
6		Water absorption	(%)	Average value ≤ 3 individual ≤ 3.3	< 3 < 3	Qualified	
7		Breaking strength	N	When thickness ≥ 7.5mm the Average value ≥ 700	>700	Qualified	
8		Rupture modulus	Mpa	Average value ≥ 30 individual ≥ 27	> 30 > 30	Qualified	
9		Abrasion resistance	revs	> 1500	> 1700	Qualified Class 3	
10		Scratch resistance	MOH	—	> 6	Qualified	
11		Frost resistance	—	No cracking after test	conformed	Qualified	
12		Resistance to acids & alkalis	—	not less than grade GB	Grade GA	Qualified	
13		Chemical resistance	—	not less than grade GB	Grade GA	Qualified	
14		Slip resistance	R	Ramp slip rating test	R11	Exterior	
			DcoF	DCoF: 0.42	>0.42	Matt/Exterior	



Italian ink-jet design Gres Porcelain floor & wall tiles

KREM

REINE



Beige



Ivory

Grey



REINE is available in 60x60cm / 24x24", 30x60cm / 12x24" and 60x120cm / 24x48" in Matt, Polished & External Finishes.

Packaging:
600 x 600mm x 10mm 4pcs. / ctn. 1.44m² / ctn. 30kg / ctn. 1,1 x 1,1m pallet: 40ctn. / pallet 57.6m² / pallet
24 x 24" x 0.39" 4pcs. / ctn. 15.5 sqft / ctn. 66.14 lbs / ctn. 3' 6" pallet: 40ctn. / pallet 620 sqft / pallet

KREM